

Guidelines for Completing the Exterior Shutter Order Form

# PLEASE MAKE COPIES OF THE PRICE QUOTE / ORDER FORM

Fax to (334) 264-6001 • Call: (334) 264-6158 • Email sales@southernshutter.com

### **CUSTOM OPTIONS**


- Rail Placement: Distance from bottom of shutter to bottom of rail. Rails often align with window elements such as, lock rail, transoms, muntins and are, sometimes used to achieve a design independent of window layout. Two equal sections are standard.
- Custom Options: Southern Shutter Company can build your shutters to meet your specifications. Select from the options table listed on the price page for your specific shutter type.

### SPECIAL INSTRUCTIONS

- Arch Height: Provide low and high point of arch or radius
- Hardware: Specify using codes from Exterior Hardware Catalog Page. Refer to Getting Started section of catalog for hardware specification.
- Combination Shutter Options: Combining louver and panel sections is a common design variation. Indicate your layout from top to bottom. (Example: Louver over panel — L/P) Use Louver Panels Codes from Order Form.


### **BAHAMA/SPANDREL SHUTTERS**

- Sold Per Each (Bahama Width = Width of single shutter panel x 2) Example: 48" wide Bahama = 24" pair price
  - plus \$132.00 Bahama construction fee.
- Available in 1 3/8" Designline and Heavy Duty product lines.
- · Movable louver shutters are limited to one substile.
- Oversize panels are best broken down into multiple sections for ease of shipping and installation, as well as appearance.
- Stabilizing bars may be used on panels with or without substiles to produce wider louver sections and prevent louver bowing.
- Additional substiles available in all fixed and paneled lines.



### **BOARD & BATTEN SHUTTERS**

- Standard Board Gap: 1/8"
- · Vertical Boards Board width determined by overall shutter width and number of boards as specified by the customer.
- Horizontal Battens 1" thick x 3 ½" wide
- · It is recommended that board & batten Shutters over 42" in height be constructed with 3 horizontal boards.





• Guidelines for Completing the Exterior Shutter Order Form •

Please follow these step-by-step guidelines in completing the enclosed Exterior Price Quote/Order Form.

### PLEASE MAKE COPIES OF THE PRICE QUOTE/ORDER FORM

Fax to (334) 264-6001 • Call: (334) 264-6158 • Email sales@southernshutter.com

### QUANTITY

- Pairs: Shutter panels are priced and sold in pairs.
- Bahama Shutters: Shutter panels are priced and sold per each.

Example: 48" wide Bahama = 24""pair price plus \$132.00 Bahama construction fee.

### **MEASURING**

- Room/Window Location Indicate the window location.
- Measurements
- Opening Width: Window openings are not always perfectly square.

Measure the shutter pocket/opening width at the top and bottom of the window.

Record smaller dimension

- Opening Height: Measure the shutter pocket/opening height at the left and right sides of the window. Record smaller dimension.
- Shutter Width: Allow for clearances and overlaps record panel width desired (generally less than pocket) ÷ 2. See color catalog page "Getting Started" (T6) for specific measuring details.
- Shutter Height: Allow for clearance (generally off pocket length).

### **SPECIFYING**

- SHUTTER STYLE
- LOUVER OR PANEL OPTIONS
- 1 3/8" Designline Fixed Louvers / Panels
  - Traditional Fixed Louver 1 1/8", 2 1/2", 3 1/2" wide x 3/8" thick
  - European Fixed Louver 1 3/4", 2 1/4", 3 1/4" wide x 3/8" thick
  - · Single or Double Sided Raised Panel or Flat Panel. V-Groove option available.
- 1 3/8" Heavy Duty Fixed or Movable Louvers / Panels
  - Traditional Fixed 1 5/8" wide x 3/8" thick
  - Traditional Movable Louver 1 1/8", 2 1/2", 3 1/2" wide x 3/8" thick
  - Single or Double Sided Raised Panel or Flat Panel. V-Groove option available.
- 1 1/2" Standard Fixed Louvers / Panels
  - Traditional Fixed Louver 1 3/8" wide x 1/4" thick
  - Single or Double Sided Raised Panel or Flat Panel. V-Groove option available.

## **FINISHING OPTIONS**

- Unfinished
- · Primed light sanding recommended
- Primed & Sanded primed; sanded and joints sealed; ready for finishing
- Primed & Finished note color specification at bottom

See color catalog page "Beyond the Basics" for exterior finish option details.



# Southern Sh Telephone: Fax: 1-3

STYLE CODE

Board & Batten Shutters

Indicate in Special Instructions.

☐ Number of Vertical Boards
☐ Number of Horizontal Boards

☐ Z-Bar Configuration

Single-sided Panel

☐ TFS 1-3/8"
☐ SR Raised
☐ DR Raised

□ **SF** Flat □ **DF** Flat

☐ SV V-Groove Option☐ DV V-Groove Option

Special Instructions. Use codes from

Hardware Price Sheet.

1-1/4" x 3/8" Decorative Trim 4
Available on flat panel only.

Indicate hardware selections in the

SHUTTER HARDWARE

Double-Side Panel

□ST

1-1/8" Standard Shutters Traditional Fixed Louver 1/4" thick

# Email: sales@s

	EXTERIOR SH	EXTERIOR SHUTTER PRICE QUOTE/ORDE	UOTE/ORDER FORM		Check One: Quote Order	der
	Business Name		Purchase Order No.		Date	
hern Shutter Company	Address		City		State Zip Code	
Fax: 1-334-264-6001	Contact Name			Telephone (		
: sales@southernshutter.com	Fax ()	Email				
SHUTTER STYLE			FINISHING OPTIONS	Code	TRIM OPTIONS Code	-10
DESCRIPTION	LUUVER/PANEL OP HUN CUDES		Unfinished	UNF		. 1
1-3/8" DesignLine Shutters Traditional Fixed Louver 3/8" thick	☐ <b>TF1</b> 1-7/8" ☐ <b>TF2</b> 2-1/2"	□ <b>TF3</b> 3-1/2"	Spray Primed - Light Sanding Required   EPC	□ EPC	OR Control Control	ىد
European Fixed Louver 3/8" thick		□ <b>EF3</b> 3-1/4"	Primed & Sanded	□ EPS	3/0 whater notified	
Single-sided Panel	☐ SR Raised ☐ SF Flat	☐ <b>SV</b> V-Groove Option	Primed & Finished	FIN	3/8" Half Round	ىد
1-3/8" Heavy Duty Shutters			COMBINATION SHUTTER OPTIONS			
Traditional Fixed Louver 3/8" thick	]		Notate in Special Instructions		3/4" x 3/8" Decorative Trim 1	
Iraditional Movable Louver 3/8" thick Single-sided Panel	☐ SR Raised ☐ SF Flat	☐ SV V-Groove Option	Louver over Panel: Panel over Louver:	□ P/L	□ D2	
Double-Side Panel	□ <b>DR</b> Raised □ <b>DF</b> Flat	□ <b>DV</b> V-Groove Option	Louver over Louver over Panel: Other:		3/4" x 3/8" Decorative Trim 2	
1-1/8" Standard Shutters			Other:	L	,	

	SPECIAL			Pr/Ea	QTY
	SPECIAL INSTRUCTIONS			North 1	Window Opening Opening Shutter Location Width Height Width
	SNO			36"	Opening Width
				72"	Opening Height
				18"	Shutter Width
				71.5"	Shutter Height
				DL	Shutter Style
				EF2	Shutter Shutter Louver or Finishing Rail Placement Height Style Panel Option Option RP1 RP2 RP3
				EPC	Finishing Option
				34"	Rail RP1
				63"	Place RP2
				-	ment RP3
Color NoSheenSheenSheonSheon	PAINT MANUFACTURER _			Copper Capping, 1/2" Shiplap	Custom Options See Price Sheet
Formula				Arch Top: High 71.5", Low 53.5"	SPECIAL INSTRUCTIONS For additional instructions, please use space below

3/4" x 3/8" Decorative Trim 3

□ D3

□ 04